AL.1.54/..

- **replaceable expansion insert**
- **non-PVC**
- **stable aluminum supports**



FEATURES
expansion insert can be replaced anytime, abrasion-, weather- and temperature-resistant (-40°C to +120°C), perforated bearing legs guarantee the best connection to the substrate/covering

APPLICATIONS
residential, office and administration buildings

MATERIAL
aluminium, EPDM expansion insert

COVERING TYPES
coating, screed, natural and stone slabs

FORMED PARTS
corner piece, T-piece, cross piece, floor-wall connections

NOTES
For mastic asphalt, please ask for technical advice.

TECHNICAL DATA

Movement horizontal:	16 mm (±8 mm)
Movement vertical:	12 mm (±6 mm)
Visible width:	54 mm
Maximal joint width:	40 mm
Load rating:	wheel load 700 kg up to Ø 150 mm, B = 100 mm
Supply length:	3 mtr
Color of expansion insert:	schwarz

DESIGNS

ARTICLE NO.	PROFILE HEIGHT (h)	RECESS (BxT)
AL.1.54/20	20 mm	210 x 30 mm
AL.1.54/33	33 mm	210 x 43 mm
AL.1.54/50	50 mm	210 x 60 mm
AL.1.54/63	63 mm	210 x 73 mm
AL.1.54/83	83 mm	210 x 93 mm
AL.1.54/103	103 mm	210 x 113 mm
AL.1.54/123	123 mm	210 x 133 mm

Special heights on request.



AL.1.54

Subject to technical change without notice.